bioscrypt


V-PRO:











The reader matches that the fingerprint of the person seeking entry match the identity of the card-holder. This dual factor solution combines a self-contained fingerprint verification module and an HID proximity card reader.

Benefits

- Self contained units performs enrollment, verification and stores up to 4000 fingerprints
- User-friendly installation with pigtail connections and single gang or mullion mount compatibility
- Flexible communication options including RS232, RS485 and Wiegand
- Simple and quick enrollment of fingerprints, less than 3 seconds
- Advanced technology maintains verification accuracy with dirty, cut, scarred, aged, wet or dry fingerprints
- Provides dual factor authentication, a proximity card, something you have and your fingerprint, something you are
- Multiple administration options including standalone (using enrollment and delete card in proximity mode), roaming (a laptop PC temporarily connected to the V-Prox), or Network (RS485, RS232 and ethernet)
- Intuitive user interface with red, green and amber LED and tone signals
- Built-in Compatibility with industry standard Proximity card infrastructures



bioscrypt™











Distributed By:

Access Controls International Freehold, New Jersey 07728 USA

T 888 810 6060

F 732 462 0511

www.acisecurity.com

Bioscrypt Inc, Bioscrypt, Bioscrypt on Board, Bioscrypt Network, Bioscrypt Portable, Bioscrypt Core-PC, Bioscrypt Core-Wireless, ¿Pass, V-Smart, V-Prox, V-Flex, MV1200 are all trademarks or registered trademarks of Bioscrypt Inc.

> bioscrypf on board

Mounting Specifications

Mounting Specifications Flat surface, Single Gang or Mullion. Mountable Holes in wall mount plate will accept #6 screws or bolts. Clearance hole diameter is .155". Trim plate included to cover single gang box.

Specifications:

Dimensions: Length: 130 mm (5.12")

Width: 50 mm (1.97")
Depth: 65.5 mm (2.5")

Communications: Pigtail Wire Connection for RS232,

RS485, Wiegand IN/OUT

Enrollment Time: < 3 second Verification Time: < 1 second Equal Error Rate (EER): 0.1%

Number of Templates: 4000 per unit
Template Size: < 350 Bytes
Current Draw: Idle: 0.15 amps @ 12V
Enroll / Verify: 2 amps @ 12V
Voltage: 7 to 12 volts DC

Ordering Information

VPRX-HD: V-Prox with HID integrated proximity reader

VDSPLY-H: Display kit/HID: Stand, Data Sheets, 5 HID cards, Power Supply **BIO-SDK:** Common Development Software CD (Supports MV1200, V-Prox,

V-Flex, V-Pass)

About Bioscrypt Inc.

Bioscrypt Inc. (TSE:BYT) is an established provider of advanced fingerprint technology that enables simple and secure access to facilities and information. The company deploys its fingerprint solutions through product sales and technology licensing. To date, over 25,000 Bioscrypt readers are installed, providing enhanced building security.

The symbol bioscrypt on board™ signifies that Bioscrypt Inc.'s high standards of biometric quality and security reside within that product.

